

**METHOD AND SYSTEM FOR TESTING FOAM-WATER
FIRE PROTECTION SYSTEMS**

- [01] This application claims priority to provisional U.S. Application Ser. No. to be assigned, METHOD AND SYSTEM FOR TESTING FOAM-WATER FIRE PROTECTION SYSTEMS, inventor Tom Boyle, filed November 9, 2001.

FIELD OF THE INVENTION

- [02] The invention relates to a fire suppression system, more particularly to foam-water fire protection systems, and most particularly to a method and system for testing foam-water fire protection systems.

BACKGROUND OF THE INVENTION

- [03] Many types of suppression systems currently exist. Of these, a great portion of these systems are dedicated to extinguishing fires or blanketing a spill where the material is of a type that water alone will not suffice. Often, these systems utilize a foam, typically a foam concentrate mixed with water via a proportioning valve such that the water mixes with and carries the foam through the system.
- [04] As with all fire suppression systems, it is the hope that the system is infrequently, if ever, needed to suppress a fire or prevent a hazardous spill from igniting. However, because of a lack of use, it is often uncertain whether fire suppression systems are in proper working order. In addition, a lack of use may lead those in control of the systems to neglect proper maintenance and testing.
- [05] One issue present with testing of a fire suppression system is the labor and cost involved. With foam-water suppression systems, typical testing methods involve sending foam through the proportioner and/or other parts of the system, and measuring the flow (volume and rate) of the mixture. The foam is specially formulated, must be purchased at an expense, and cannot be recycled. In addition, the

use of the foam in testing results in an expensive disposal issue of the foam and water mixture due to environmental regulations. Furthermore, typical testing systems are cumbersome and laborious, as is the process itself. These factors further contribute to an inclination by some to delay proper testing and maintenance, or forego such altogether.

[06] There is a variety of foam-water fire suppression systems. Two types are commonly referred to as an In-Line Balanced Pressure Proportioner system, or ILBP, and a Bladder Tank Proportioner system. Both of these rely on a source of foam concentrate and a source of water (fire protection water supply). Often times, the foam concentrate is stored in, for instance, a bladder tank. In both of these types of systems, as well as others, a valve known as a proportioner controls the mixing of the foam concentrate and water. Once the mixture passes through the proportioner, it is then forced through a portion of the fire suppression system containing sprinklers or other devices for applying the foam/water mixture to the area of concern, either a fire or a hazard with potential for fire. In these systems, it is of great concern that the levels are properly mixed, a fact that relies to some degree on pressure on the valve and in the lines providing the water and foam concentrate. This requires being able to test the effectiveness and proper working order of the proportioner and of the system in general.

[07] As an international standards organization, the National Fire Protection Association (NFPA), of Quincy, MA, has developed standards for the testing of various fire equipment. Among these standards is Standard 25, Standard for Inspection testing, and Maintenance of Water-Based Fire Protection Systems. The neglect of maintenance and testing of fire protection and suppression systems is a serious issue, and it has long been desired to be able to test the systems easily and without a great expense.

BRIEF SUMMARY OF THE INVENTION

- [08] In accordance with one aspect of the present invention, a test system 10 for testing a fire suppression system 100 for a determination of a flow ratio of at least two different constituents 2, 4 where the fire suppression system 100 is of a type that mixes the flow of the at least two constituents 2, 4 for distribution whereby only one of the two constituents 2, 4, is required for testing. The test system 10 comprises a control box 14, a first constituent flow meter system 16, and a second constituent line flow meter system 18, wherein the first constituent 2 is directed through the first constituent flow meter system 16, the first constituent 2 is directed through the second constituent line flow meter system 18, each flow meter system 16, 18 detecting a flow rate therein, and the control box 14 compares the flow rates of the first constituent 2 through each flow meter system 16, 18, and indicates the flow rate ratio had the second constituent 4 been directed through the second constituent flow meter system 18.
- [09] The test system 10 is preferably portable, and may be connected and disconnected to the fire suppression system 100. The control box 14 is preferably waterproof and includes a pair of flow rate meters 30, 32. The test system 10 of can include a recording means 12, preferably a flatbed recorder. The first constituent flow meter system 16 receives the first constituent 2 from a fire protection first constituent supply source 15 at a flow rate appropriate for actual fire suppression conditions, and the second constituent line flow meter system 18 receives the first constituent 2 from a water balance line 122. The test system 10 can include a booster pump 312 between the second constituent line flow meter system 18 and the water balance line 122 thereby providing the first constituent 2 with an inlet pressure to the second constituent line flow meter system 18 appropriate for actual fire suppression conditions to an outlet pressure from the second constituent storage 102. The test system 10 is designed so that the first constituent 2 may be discharged from the test system 10, or may be recovered. A nozzle 230 can be provided on the discharge for providing a sufficient pressure to the test system 10. In a preferred embodiment, the first constituent 2 is water and the second constituent 4 is foam concentrate.

- [10] In a second preferred embodiment, a test system 10 is provided as above, with the additional ability of measuring the actual flow rate of the mixed constituents 2, 4 by directing the mixed flow through the test system 10, and a probe 58 is located in the path of the mixed flow. The probe 58 can be connected to a conductivity controller 34 located in the control box 14, the control box 14 displaying a reading of the flow by correlating the conductivity of the mixed flow to a conductivity of the two constituents 2, 4 based on the proportions of the two constituents 2, 4 present in the flow. This second embodiment may be utilized to determine the actual proportions of the two constituents 2, 4 in the mixed flow where both constituents 2, 4 are sent through the fire suppression system 100, or may be utilized as a verification tool and calibration means for the test system 10.

BRIEF DESCRIPTION OF THE DRAWINGS

- [11] In the drawings, Fig. 1 is a perspective view of a preferred embodiment test system of the present invention;
- [12] Fig. 2 is a representational view of a fire suppression system with a flow meter of the test system of the present invention attached thereto;
- [13] Fig. 3 is representational view of a flow meter of the test system of the present invention attached to a concentrate line and a water inlet pipe;
- [14] Fig. 4 is a perspective view of a hose nozzle of the present invention; and
- [15] Fig. 5 is side elevation view of the hose nozzle of the present invention.
- [16] Corresponding reference numerals will be used throughout the several figures of the drawings.

DETAILED DESCRIPTION OF THE INVENTION

- [17] Referring initially to Fig. 1, a test system 10 of the present invention is depicted including a chart recorder 12, an electronics control box 14, a water flow meter

system 16, and a concentrate line flow meter system 18. The test system 10 is relatively small and compact. Accordingly, it can be mounted and transported for simple use and on-site deployment, as is pictured here on a test stand 22. In a preferred embodiment, the test stand 22 is a 4-foot by 6-foot cart with wheels 24 and a handle 26. The test system 10 measures the flow rates of two constituents 2 and 4 (see Fig. 2), principally water and foam concentrate, though others may be substituted as per the requirements of a fire suppression system 100 (see Fig. 2).

- [18] The recording means 12, such as a chart recorder, is used to record the measurements taken by the test system 10. In the present embodiment, a compact flatbed recorder is employed such as the RD 6100 2 pen chart recorder manufactured by Omega Engineering, Inc., of Stamford, CT. It should be noted that the purpose of recording the test results may be either to make calculations based upon the results, or to establish proof of the testing. It should also be noted that other recording means may be employed, including other types of hard-copy (paper) recorders, or another means for recording data, such as magnetic tape or digital (computer/microprocessor) based recorders.
- [19] The electronics control box 14 includes, in a preferred embodiment, a weather-proof enclosure since many of the uses of the system 10 are tests performed outside of any protective enclosure, as well as the fact that the system 10 is measuring the flow of large amounts of water under pressure, water which could damage electronic components located within the control box 14. The control box 14 measures 20" x 20" x 10," thereby providing space for electronics contained therein. Preferably, the electronics control box 14 includes a power source rated at least about 110 VAC.
- [20] The electronics control box 14 contains a first flow rate meter 30, and a second flow rate meter, herein referred to as the concentrate meter 32. In the present embodiment both flow rate meters 30 and 32 are manufactured by Omega Engineering, Inc. and are sold as the DPF701 Series Rate Meter/Totalizer. The control box 14 also includes a conductivity controller 34. In a preferred embodiment, the conductivity

monitor/controller 34 is manufactured by Omega Engineering, Inc. and sold as the CDCN-90A and is microprocessor based.

- [21] The first flow meter system 16 includes two sections of pipe 40, 42 with a water supply meter 44 mounted therebetween. In a preferred embodiment, each pipe 40, 42 is a 4" Schedule #40 BLK pipe, and the supply meter 44 is a turbine meter manufactured by the Omega Engineering, Inc. and marketed as a FTB-740, though other pipes and meters would also suffice. The preferred turbine meter has a flow meter range of 6-1100 gallons per minute (GPM). The first constituent flow meter system 16 has an inlet end 46 and outlet end 48. Each end of the flow meter system 16 includes hose connections 50. Preferably, the hose connections 50 are 2-1/2" hose connections with National Standard Hose Threads (NSHT). As depicted, each hose connection 50 is covered with a standard hose cap 52. Along the length of pipe 42 is an outlet 56 into which is inserted (in the internal flow path of the pipe 42) a probe 58 of the conductivity monitor/controller 34. In the present embodiment, the Omega Engineering, Inc. manufactured CDCN-90A is used for the conductivity monitor/controller 34, as mentioned above.
- [22] The concentrate flow meter system 18 is connected to the control box 14. The concentrate flow meter system 18 is preferably a 2" stainless steel flow meter 19 rated at 250 p.s.i., such as that manufactured by Omega Engineering, Inc. and marketed as FTB720 with a flow rate range of 2-300 GPM. The flow meter 19 is then connected to the electronics control box 14.
- [23] Referring now to Fig. 2, a typical fire suppression system 100 of the type utilizing a foam concentrate bladder tank system 102, also referred to as a bladder tank foam water system, is depicted. The bladder tank system 102 stores second constituent 4, typically foam concentrate, for the event the second constituent 4 is needed by the fire suppression system 100. Fig. 2 includes arrows indicating the direction of flow through various pipelines. The fire suppression system 100 depends on a fire protection first constituent supply 105 feeding into a supply pipe 106. The supply

pipe 106 connects to a proportioner 108. The proportioner 108 is a valve as well as a mixer, in the sense that the proportioner 108 mixes supply of first constituent 2 with supply of second constituent 4 (foam concentrate) at the proper ratio. The proportioner 108 is also connected to a hazard pipe 110. The hazard pipe 110 feeds sprinkler system (see Fig. 6) or other means for dispersing the first and second constituent mixture (water/foam concentrate) by the fire suppression system 100. Feeding directly into the proportioner 108 is a foam concentrate outlet line 120. The foam concentrate outlet line 120 conveys foam concentrate directly from the bladder tank system 102 to the proportioner 108 for mixing. The bladder tank system 102 can include features known in the art, such as a fill connection 115, a pressure vacuum vent 116, and a tank drain valve 117.

- [24] As depicted, the fire suppression system 100 requires balanced pressure between the first and second constituents 2, 4 (water and foam concentrate). The fire suppression system 100 includes a water balance line 122 and a foam concentrate balance line 124 represented with a valve 126 between the balance lines 122, 124. Preferably, the valve 126 is a diaphragm control valve providing automatic pressure balance.
- [25] Under fire suppression conditions, foam concentrate (second constituent 4) would be permitted to exit the bladder tank system 102 at an exit valve 130 along a concentrate feeder line 132. The concentrate feeder line 132 is connected to a valve 134, which is in turn connected to an intermediate feeder line 136. The intermediate feeder line 136 connects to a concentrate pressure regulating valve 138, which is in turn connected to the foam concentrate outlet line 120. The concentrate pressure regulating valve 138 is preferably a 2" water power ball valve. When the system 10 is in use, the concentrate pressure regulating valve 138 is actuated by the return flow exiting the concentrate flow meter system 18.
- [26] The flow meter 19 of the concentrate flow meter system 18 of the test system 10 connects to an inlet line 150 and an outlet line 152. The inlet line 150 connects to the water balance line 122, and the outlet line 152 connects to the intermediate feeder line

136. As such, water from the balance line 122 flows through the concentrate flow meter system 18, through the proportioner 108, and into the hazard pipe 110. In this use of testing, valve 134 is closed.

[27] During testing as described, the water flowing through the hazard pipe 110 flows to a test outlet pipe 170. It should be noted that, under non-testing conditions, the flow through the hazard pipe 110 would be a mixture of foam concentrate and water, and the flow would not pass through the test outlet pipe 170, instead being directed to the sprinklers or other foam dispersing means through the hazard pipe 110 as at location 172. The test outlet pipe 170 has at its terminus a solution control valve 174 which connects to test stand line 176. The test stand line 176 connects to, for instance, a hose 178 (see Fig. 6) which connects to the hose connection 50 of the inlet end 46 of the water flow meter system 16 (see Fig. 1).

[28] Referring now to Fig. 3, an exemplary use of the system 10 is depicted having the concentrate line flow meter system 18 and flow meter 19 connected to a fire suppression system 200. Foam concentrate (second constituent 4) is stored in a concentrate tank (Fig. 2) and is delivered via a foam inlet pipe 204. Water (first constituent) is delivered from a water supply (Fig. 2) and delivered via a water inlet pipe 206. A concentrate isolation valve 208 connects to the foam inlet pipe 204 located on the foam inlet pipe 204, the concentrate isolation valve 208 having an open/close locking capability. When testing, the concentrate isolation valve 208 is locked in closed position. A tee 210 is connected to the concentrate isolation valve 208, to the flow meter 19, and to a concentrate line 212. The flow meter 19 is additionally connected to a drain supply 214 from the water inlet pipe 206. When testing, water flows through the flow meter 19 into the tee 210 and into the concentrate line 212 instead of the foam concentrate. A balancing valve 216 is located on the concentrate line 212 for insuring that proper pressure flow through the concentrate line 212 is maintained. After the flow through the flow meter 19 and concentrate line 212 passes through the balancing valve 216, it enters a proportioner 218. As depicted, a retard chamber 220 actuates a water powered ball valve 222.

When the fire suppression system 100 is tested or activated, water flows through the water inlet pipe 206, and the ball valve 222 is actuated by the retard chamber 220 to open the concentrate line 212 so that the foam concentrate (during fire suppression conditions) or water (during testing conditions) passes through to the proportioner 218.

- [29] After the proportioner 218, the combined flow from the concentrate line 212 and the direct flow from the water inlet pipe 206 flow through a ball valve 224 and into a test outlet pipe 226 to the hose connection 50 (see Fig. 1).
- [30] Referring now to Figs. 4 and 5, a hose monster 230 is depicted. The hose monster 230 is a nozzle manufactured by Hydro Flow Products, Inc. of Rolling Meadows, Illinois. In order to properly connect to an outlet hose 320 (see Fig. 6), the selected hose monster 230 preferably has an inlet diameter 232 of 4 inches. Furthermore, the hose monster 230 has an outlet diameter 234 of 6", a outlet length 236 of 23", and inlet length 238 of 15", and an overall weight of 27 pounds. The hose monster 230 is necessary to provide the proper pressure on the flow of water.
- [31] Fig. 6 is a diagram of one embodiment and use of the present invention. As depicted, there is an existing structure 300 above which is located an existing sprinkler system 302. Connecting to the sprinkler system 302 is a concentrate line 304 for delivering foam concentrate to the system, as well as a water flow connection 306 for delivering water. The concentrate line 304 and a main drain 308 of the sprinkler system 302 connect to the concentrate flow meter system 18 (flow meter 19). Flow of water passes from the main drain 308, through a booster pump 312 and flow meter 19, and returns to the concentrate line 304 where it passes through a proportioner (Figs. 2, 3). The proportioner combines this flow with the main flow of water from the water supply. It should be noted that in bladder tank systems, the booster pump 312 is unnecessary because the existing water pressure supplied for the system 10 is the same pressure as would be exerted on the bladder tank. Thus, the amount of foam that would be displaced by the pressure is the same as the pressure of the water being

injected in place of the foam concentrate. Combined flow from the proportioner passes through the test system 10 at the test stand 22 (Fig. 1) and into an outlet hose 320 and is discharged from the hose monster 230.

- [32] It is known that each fire suppression system of the types to which this system 10 is applicable require a proportional flow of water to foam concentrate. Each fire suppression system is provided with specific relative flow rates. Often, these fire suppression systems are specifically designed and built for a particular location, similar to the way that of air conditioning and heating systems (HVAC) systems are. The rates of flow for water and foam concentrate are dictated by the test and the characteristics of the foam itself. The flow rate for water is measured by the test system 10 by outletting the actual water of the system through the test stand line 176 (see Fig. 2) connected to the hose connection 50 of the inlet end 46 of the water flow meter system 16 (see Fig. 1). The flow rate of the foam concentrate is measured as the water supply system provides pressure (which may be boosted by the booster pump 312 as shown in Fig. 6) through the water balance line 122. The system 10 includes inlet line 150 connected to the water balance line 122. The inlet line 150 directs water from the water supply through the flow meter 18, thereby indicating the rate of flow water substituted for the foam. The components of the control box 14 then compare the flow of the water through the water flow meter system 16 to the flow of the water through the flow meter 19 to provide a reading of the relative flow rates. Thus, the test system 10 identifies proportional flow rates of the water supply and the foam concentrate. The percentage of the total flow through the water flow meter system 16 that is due to the flow through the flow meter 19 can be calculated using the measured total flow through water flow meter system 16 and the measured flow through the flow meter 19. This is accomplished without discharge of any foam concentrate, and the resulting water can be dispersed through the hose monster 230.
- [33] Furthermore, the probe 58 of the conductivity monitor/controller 34 is provided for measuring actual foam/water mixture flow. (Fig. 1). In this manner, the fire suppression system actually releases foam concentrate mixed with water through the

water flow meter system 16. The probe 58 measures the conductivity levels of the resulting mixture, thereby determining whether the proper mixture of water and foam concentrate is being delivered by the fire suppression system.

- [34] While the invention has been described with respect to specific examples including presently preferred modes of carrying out the invention, those skilled in the art will appreciate that there are numerous variations and permutations of the above described systems and techniques that fall within the spirit and scope of the invention as set forth in the appended claims.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
22